

RECOMMENDATION CHART

SNo	SERIES	DRY RUNNING (UPTO 350 MM IMM. DEPTH)	APPLICATION									MEDIUM					CONTAMINATION			IMPELLER TYPE					
			HIGH TEMPERATURE	CHILING	BORING	SAWING	MILLING	TURNING	GRINDING	CIRCULATING	WASHING	EMULSIONS	COOLANT & LBRCTS	WATER	DE IONISED WATER	SOLVENTS	CHEMICALS	COARSE	MEDIUM	FEW	SEMI OPEN	CLOSED	CASTED	SHEET METAL FABRICATED.	PERIPHERAL
1	RV25....250	X	/	X	X	X	X	X	X	X	X	X	X	/	/	/			X	X	X		X		
2	RK275..800	X	/		X	X	X	X	X	X	/	X	X	/	/	/		X	X	X	X		X		
3	RK3.5....7		/		X	X	X	X	X	X	/	X	X	/	/	/		X	X	X		X	X		
4	RKC100....500		/		X	X	X	X	X	X	/	X	X	/	/	/		X	X	X		X	X		
5	RKM200 RKM300				X	X	X	X	/	X	/	X	X	/	/	/			/	X		X	X		
6	RKM100,RKM250 RMS400-800	X	/		X	X	X	X	X	X	/	X	X	/	/	/			X	X	X		X		
7	RR50	X	X		X	X	X	X	X	X	/	X	X	/	/	/			/	X			X		X
8	RMB-V-50..100				X	X	X	X	/	X	/	X	X	/	/	/	/			X	X		X		
9	RKM060, RK 060			X	X	X	X	X	X	X	X	X	X	X	X	/			/	X			X		
10	RMH 060, 0250			X	X	X	X	X	X	X	X	X	X	X	X	/			/	X		X		X	
11	RTA		X	X	/	/	/	/	/	X	X	X	X	X	X	X	/			X					X
12	RKM 0250, 050			X						X	/	X	X	X	/	/			X	X		X	X		
13	RPP				/	/	/	/	/	X	/						X				X				
14	RTH4 & RTH2			X	X	X	X	X	/	X	X	X	X	X	/	/				X		X		X	

X - USABLE

/ - PLEASE ASK BEFORE SELECTING

NOTE :

CONTAMINATION
Handled by pumps

TYPE

PARTICLE SIZE

Percentage of contamination
against coolant volume

COARSE

> 1MM

5%

MEDIUM

0.2 TO 1 MM

2%

FEW

< 0.2

< 1%